



NBR Rubber 3 Ply Waterproof Sealing Tape

A high grade waterproof sealing tape system for interior and exterior domestic and commercial applications consisting of:

- 10m / 50m Tapes
- Internal / External Corners
- Pipe Inlet Collar

DESCRIPTION

A specially coated 120mm wide 3 ply tape consisting of 2 outer polyester fleece layers and a flexible 70mm wide NBR rubber elastic core. Promotes excellent bonding with ROCATEX Waterproof Tanking Coat.

APPLICATION

To be used in conjunction with ROCATEX Waterproof Tanking Coat - please refer to separate technical data sheet.

Apply first coat of ROCATEX Waterproof Tanking Coat and whilst still wet firmly press in the sealing tape / corners / pipe collars. Ensure there is an overlap of at least 50mm. Once dry (approximately 15 minutes) a second coat should be applied. Ensure that the tape is fully covered with ROCATEX Waterproof Tanking Coat. Tiling can commence once the second coat has fully cured, approximately 1 hour at 20°C.

Suitable for medium to high loads of non-pressurized water (e.g. showers, wetrooms, bathrooms, steam rooms - both domestic and commercial). It can also be used for water under constant positive pressure, both internally and externally (e.g. swimming pools, balconies and terraces).

TECHNICAL DATA

Substrate:	2 outer layers of polyester fleece
Coating:	NBR rubber
Colour:	Grey
Total width / Coating width:	120mm / 70mm
Total thickness (approx.):	0.6mm
Material weight (approx.):	50g/m
Length per roll:	10m / 50m
Water pressure resistance:	Leakproof at 3 bar
Elongation, lateral direction:	250%
Elongation, lengthwise direction:	50%
Resistance to temperature, min. / max:	-20°C / +90°C